

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Patent Application of

BRIAN McGUIRE

Application No. 09/972,896

File: October 10, 2001

For: WIND SHEAR DETECTION  
SYSTEM



BOX MSP

Group Art Unit: 2877

**PRELIMINARY AMENDMENT**

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Prior to examination, please amend the subject application as follows.

**IN THE CLAIMS**

Insert new claims 11--13 as follows:

11. [New] A method of detecting a dangerous localized condition in an atmosphere in front of an aircraft, the method comprising the steps of:

- (a) projecting a series of optical pulses into an atmosphere ahead of the aircraft;
- (b) detecting a series of reflected optical responses from the atmosphere corresponding to reflections from predetermined distances in front of the aircraft;
- (c) processing said reflected responses to determine a current relative wind speed at said predetermined distances in front of said aircraft; and

(d) processing said current relative wind speeds to determine if a dangerous localized condition exists in front of said aircraft.

12. [New] A detection system for detecting the presence of a dangerous localized condition in front of an aircraft, said system comprising:

a laser for transmitting a first portion of a series of optical pulses in front of said aircraft;

a receiver for detecting back scattered light from said transmitted optical pulses;

delay means for delaying a second portion of said series of optical pulses for a time period substantially corresponding to the time of flight of said back scattered light; and

first comparison means for comparing said delayed second portion with said back scattered light so as to determine a wind velocity and direction, relative to said aircraft at a series of distances corresponding to said time of flight of each pulse; and

second comparison means for comparing the wind velocity at said series of distances to determine if a dangerous localized atmospheric condition is present.

13. [New] A detection system to predict the presence of a dangerous localized atmospheric condition along the flight path of an aircraft during the critical landing and take off phase comprising:

high powered solid state laser for transmitting a light beam; and

receiver to capture a second back scattered light beam from the first beam; and

a means to provide a third light beam as a sample of the first beam; and

solid state module to delay said third beam for a time corresponding to the transit time of the second light beam and the first light beam; and

solid state detector to detect a differential response of the second light beam to the response of third light beam; and

solid state computer to record and store a wind velocity measurement.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, LLP

By

  
Alan E. Kopecki  
Registration No. 25,813

Post Office Box 1404  
Alexandria, Virginia 22313-1404  
(703) 836-6620

Date: January 31, 2002